


| | | |
|--|---|---|
| Anziehvorschrift für Zylinderkopf | 688.422 |  Das Original |
| Tightening Instructions for Cylinder Head | | |
| Instructions de serrage pour culasse | | |
| Prescripciones de apriete para culatas | | |
| | passend für / suitable for adaptable à / adaptable a | Renault |

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
Tête de vis / Cabeza de tornillo



373.281
M 11x1,5x126 E18



| | | | | |
|---|--------|--|------------------|-----------------------------|
| Anziehen/ Tightening/ Serrage/ Apriete | * ▶ | Clio, Twingo, Modus 25 Nm 25 Nm 270° ±10° | Kangoo * ▶ | 25 Nm 25 Nm 225° ±10° |
|---|--------|--|------------------|-----------------------------|

Zeichenerklärung / Explanations / Explication / Explicacion

| | | | | |
|-----------------------|--|---|---|---|
| * ★ □ ● ▶ | neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel | use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle | utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage | emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro |
|-----------------------|--|---|---|---|

Motortyp / Engine type / Type de moteur / Tipo de motor

Ø: 77,5 mm; \pm : 0,7 mm

Mot: K9K 714, 718, 740, 766, 768, 800
1,5 ltr. dCi
47-63 kW (64-86 PS)

Clio, Twingo, Modus, Kangoo

ElringKlinger AG, Max-Eyth-Str.2
72581 Dettingen / Erms. Tel. 07123/724 601

688.422