

Fuel Hose

Fuel hoses made from a cured-on twine braid for conveying petrol (E5, E10, E15, E85), diesel and bio- diesel (B10, B20).

Material: NBR (nitrile butadiene rubber) **DIN/ISO:** 73379-B
 Textile **Operating Pressure:** 10bar
Burst pressure: 30bar

Temperature range: -35 to +90°C

| Packing Type | Wall Thickness mm | Bending radius mm | Outer Ø mm | Inner diameter mm | DU | Article no. |
|---------------------------|-------------------|-------------------|------------|-------------------|-----|-------------|
| Coil | 1,9 | 40 | 7 | 3,2 | 15 | 51280232 |
| | 2 | 45 | 7,5 | 3,5 | 15 | 51280235 |
| | | | 9,5 | 4,5 | 15 | 51280245 |
| | 2,5 | 50 | 10,5 | 5,5 | 15 | 51280255 |
| | | | 12,5 | 7,5 | 15 | 51280275 |
| | 2,75 | 65 | 15 | 9,5 | 10 | 51280295 |
| 3 | 75 | | 17 | 11 | 10 | 51280311 |
| Accessories | | | | | see | DU |
| Wall Mounting, fuel lines | | | | Katalog04 | 1 | 51280660 |

