

# Fuel Hose

Fuel hoses made from a rubber top layer with reinforcement inlay for conveying petrol (E5, E10, E15, E85), diesel and bio-diesel (B10, B20). Resistant to oil, acids, heat, ozone and the effects of the weather.

|                   |                            |                            |              |
|-------------------|----------------------------|----------------------------|--------------|
| <b>Material1:</b> | NBR                        | <b>Temperature range:</b>  | -35 to +90°C |
|                   | (nitrile butadiene rubber) | <b>DIN/ISO:</b>            | 73379-A1     |
|                   | CR (chloroprene rubber)    | <b>Operating Pressure:</b> | 10bar        |
|                   | Rubber with fabric lining  | <b>Burst pressure:</b>     | 50bar        |

| Packing Type              | Wall Thickness mm | Bending radius mm | Outer Ø mm | Inner diameter mm | DU        | Article no. |
|---------------------------|-------------------|-------------------|------------|-------------------|-----------|-------------|
| Coil                      | 3                 | 50                | 10         | 4                 | 15        | 51280140    |
|                           |                   | 55                | 11         | 5                 | 15        | 51280150    |
|                           |                   | 70                | 13         | 7                 | 15        | 51280170    |
|                           |                   | 80                | 14         | 8                 | 10        | 51280180    |
|                           | 3,5               |                   | 17         | 10                | 10        | 51280210    |
| <b>Accessories</b>        |                   |                   |            | see               | <b>DU</b> |             |
| Wall Mounting, fuel lines |                   |                   |            | Katalog04         | 1         | 51280660    |

